








ACCEESSORIES



DESCRIPTION	AÇIKLAMA
Type : Translating Screw (VH-S)	Tip : Mil Hareketli (VH-S)
Max force : 250 kN (for housing)	Maks. Kuvvet : 250kN (gövde dayanımı)
Ratio : 10:1 (A) or 40:1 (B)	Gövde Malzemesi : GGG-40
Housing Material : GGG-40	Dişli Oranı : 10:1 (A) veya 40:1 (B)
Screw Size : Tr 80x10	Trapez Mil : Tr80x10
Screw Material : C45 Steel	Trapez Mil Malzemesi : C45 Çelik
Stroke : 100mm	Strok : 100mm
Input Shaft Side : Input Side (AB)	Giriş Mil Yönü : Çift Çıkış (AB)
Safety Nut : NO	Emniyet Somunu : HAYIR
Working Temperature : -10 / +60 C	Çalışma Sıcaklığı : -10 / +60 C
Nominal Input Speed : 1500 rpm	Nominal Giriş Devri : 1500 rpm
Max Input Speed : 1800 rpm	Maks. Giriş Devri : 1800 rpm
Max Input Torque (for 1500 rpm) : 140 Nm	Maks. Giriş Torku (1500 rpm için) : 140 Nm
Max Drive-Through Torque : 760 Nm	Maks. İletilecek Tork : 760 Nm
Housing Lubrication : EP2 Grease	Dişli Kutusu Yağlama : EP2 Gres
Screw Lubrication : Sentinel SR OG Grease	Trapez Mil Yağlama : Sentinel SR OG Gres

VKT250-VH-S-A/B-TRS-0100-S-AB