








ACCESSORIES



DESCRIPTION	AÇIKLAMA
Type : Translating Screw Unturning (VH-SI)	Tip : Döüş Engelli Mil Hareketli (VH-SI)
Max force : 350 kN (for housing)	Maks. Kuvvet : 350kN (gövde dayanımı)
Ratio : 40:1 (B)	Gövde Malzemesi : GGG-40
Housing Material : GGG-40	Dişli Oranı: 40:1 (B)
Screw Size : Tr 100x10	Trapez Mil : Tr100x10
Screw Material : C45 Steel	Trapez Mil Malzemesi : C45 Çelik
Stroke :100 mm	Strok :100 mm
Input Shaft Side : Input Side (AB)	Giriş Mil Yönü: Çift Çıkış (AB)
Safety Nut : NO	Emniyet Somunu : HAYIR
Working Temperature : -10 / +60 C	Çalışma Sıcaklığı : -10 / +60 C
Nominal Input Speed : 1500 rpm	Nominal Giriş Devri : 1500 rpm
Max Input Speed : 1800 rpm	Maks. Giriş Devri : 1800 rpm
Max Input Torque (for 1500 rpm) : 100 Nm	Maks. Giriş Torku (1500 rpm için) : 100 Nm
Max Drive-Through Torque : 1600 Nm	Maks. İletilecek Tork : 1600 Nm
Housing Lubrication : EP2 Grease	Dişli Kutusu Yağlama: EP2 Gres
Screw Lubrication : Sentinel SR OG Grease	Trapez Mil Yağlama: Sentinel SR OG Gres

VKT350-VH-SI-A/B-TRS-0100-S-AB